


# A10E Ethernet Switch

Enhanced L2 Metro-Ethernet Access Switch



## Product Overview

A10E is designed for Metro Ethernet access portfolio, which provides cost-effective solutions for campus, enterprise, and residential access scenarios.

The product has 8x10/100Base-T auto-sensing client interfaces and 2xSFP combo GE network interfaces, which enables flexible network deployments such as dual ring or ring + chain. The A10E also offers rich functionality that guarantees MEF-compliant E-Line, E-Tree and E-LAN services together with full suite of management and protection mechanisms for FTTX triple-play applications. Port Backup (Flex Links) feature serves as an alternative to STP - a pair of layer 2 interfaces has one interface configured as backup to other, and if the primary link fails, the backup link takes over traffic forwarding. A10E is equipped with advanced microchips that ensure carrier-class stability and reliability.

## Product Description

The Orion Networks© A10E Metro-Ethernet Access Switch supports a number of key features:

- **Network Security** - Upgraded security with port-isolation, advanced ACL, broadcast/multicast/DLF storm control, unique port loopback detection, and DHCP Client/Snooping/Option 82 functionality, IGMP RADIUS Authentication
- **Resiliency & Protection** - Supports ITU-T G.8031 linear and ITU-T G.8032 ring protection; Supports STP/RSTP/MSTP, IEEE 802.3ad Link Aggregation, and Port Backup (Flex Links) as an alternative to STP functionality with ability to backup links and balance traffic between primary and backup links
- **Carrier Ethernet Service & Management** - Supports IEEE 802.3ah Link OAM, IEEE 802.1ag end-to-end connectivity OAM and ITU-T Y.1731 end-to-end service and performance; Advanced QoS technology allows stream-marking based on CoS, DSCP and port priority; Scheduling modes including SP, WRR, SP+WRR; Support flow-based mirroring/rate-limit/redirection/VLAN swapping and rewriting
- **Multicast Functionality** - Supports IGMP snooping/proxy, multicast filtering, multicast VLAN registration (MVR) to save bandwidth and optimize corresponding services such as IPTV

## Features

Switching mode	Store and forward mode Non-blocking switching
Packet Forwarding	MTU: 9,712 bytes (default) DLF Control
Bandwidth Profile	Rate limiting: up to 1,048,576Kbps Burst configuration (Max 130KB) Ingress rate limit per port Rate limit per VLAN Increments: <ul style="list-style-type: none"> <li>• 64Kbps (64K-1M)</li> <li>• 1Mbps(1-100M)</li> <li>• 10Mbps(100-1000M)</li> </ul>
VLAN	IEEE 802.1Q VLAN: 4K active VLANs Port-based VLAN GVRP, 256 max dynamic VLAN
Storm Control	Broadcast/multicast/unicast/DLF storm control Control mode: global, bps, burst Default burst: 8KB
Multicast	1K multicast addresses Static multicast group IGMP Snooping V1/V2/V3 Multicast filtering & unknown multicast discarding Multicast VLAN Registration (MVR)
Mirror	Mirroring per port Separate mirroring configurations for ingress & egress ports
Port Loopback Detection	Auto shutdown individual ports upon fault signals Auto-detection interval can be set
MAC Address Table	16K MAC address Add/remove MAC address View MAC address statistics Search MAC address Aging time: 10-1,000,000s MAC table threshold per port MAC table limit: 1-255
Q-in-Q	Port/flexible Q-in-Q 682 flexible Q-in-Q configurable items Egress-direction VLAN-mapping

## Features

Link Aggregation	Up to 6 groups and 8 ports per group Group member max-port-number 26 Load balance based on MAC/MAC+IP Standard LACP (static only)
Flow Control	IEEE 802.3x in full duplex mode Back pressure in half duplex mode Separate configurations for ingress & egress
STP	STP, RSTP & MSTP (64 instances) 256 STG (Spanning Tree Group)
Digital Diagnostic (DDMI)	SFP digital diagnostic function
Port Backup	Supported
Transparent Relay	BPDU, DOT1X, LACP, CDP, VTP, PVST
OAM	IEEE 802.3ah OAM including discovery, link performance, remote loopback, fault detection & performance stats per OAM standards OAM Active/Passive mode, OAM MIB Variable Get function OAM Event function, Extended OAM (configure on remote switch)
SLA	Layer-2/Layer-3 SLA (frame delay, jitter & packet loss)
System Management	CLI/Telnet/SNMP/Web management 16 Layer-3 interfaces, Super VLAN, max 4K VLANs RMON1, 2, 3 & 9, Bridge MIB (RFC1493), System log, Hierarchical alarms, Link alarm per port, Keep-alive report, Fault pass through Module information management
Maintenance	Debug information output, PING, Telnet client, Port statistics Port dynamic statistics
QoS	Global CoS/DSCP to queue mapping Port priority override Port TRUST mode: CoS/DSCP/port priority Global queue scheduling with 8 queues per port Scheduling mode: SP/WRR/SP+WRR WRR weight range: 1-255 Flow statistics, Flow-based mirror/rate-limit/redirection/VLAN swapping/rewriting of 802.1p CoS, DSCP, port priority
Ethernet Ring	Orion private ring protocol Up to 8 rings 124 devices on one ring switching time ≤ 50ms

## Features

ACL	MAC/IP-based ACL ACL map (L2~L4 byte) (User-defined ACL)
Safety Features	Client classification and password protection RADIUS, TACACS+ Binding of MAC address & port, Port protection, IP source guard, Dynamic APR Inspection PPPoE agent, DOT1X IGMP RADIUS Aithentication
CFM	IEEE802.1ag/ITU-T Y.1731 protocol: up to 256 MEP, 256 MA Connectivity check (CC), Loopback (LB), Link trace (LT)
Password Recovery	Supported
Filter	ACL hardware filter Support MAC 1536 traffic streams
LLDP	Discovery remote base on link layer Get remote basic information
Error Tolerance & Redundancy	System error report Fast recovery during serious error
Scheduling	System task scheduling
MEF9 & MEF14	Supported
Time Management	Time zone, Time modification, Support SNTP & NTP
Software Upgrade	Xmodem/FTP upgrade in BootROM FTP/TFTP
Auto configuration	Supported
DHCP	Up to 6KV (CM&DM) lightning proof ability on all power and communication interfaces
Cable Diagnostic	Supported

## Specifications

Performance	Switching fabric: 5,6Gbps
Capacity	64MB DDR2 8MB flash 1.5MB switch buffer 1K IGMP groups
Indicators	Power Supply (flashing) FE port: LINK/ACT GE port: LINK/ACT
Physical interface	Management port: 1 console (RJ45) Client interfaces: 8 x 10/100 Base-TX RJ45 port Network interfaces: 2 x COMBO (2 x 100/1000Base-X SFP; 2 x 10/100/1000Base-T RJ45)
Power Specs	AC: 90~264V, 47~63Hz DC: 32-74V Full load: ≤ 12,9W
Usage Conditions	Operating temp: 0~50 °C (32~122 °F) Storage temp: -25~70 °C (-13~158 °F) Humidity: 10~90% non condensing
Dimensions	210(L) x 210(W) x 44(H) mm
Weight	1.2Kg

## Compliances

Standards & Protocols	IEEE 802.1Q VLAN, IEEE 802.3ad Link Aggregation, IEEE 802.1ad QinQ, IEEE 802.1D Spanning Tree, IEEE 802.1w RSTP, IEEE 802.1s MSTP, IEEE 802.1x Security, IEEE 802.1p CoS Prioritization, IEEE 802.3x Flow Control, IEEE 802.3ah OAM, IEEE 802.1ag Connectivity Fault Management, ITU Y.1731 Services OAM, Statc Routing, IGMP v1/v2/v3, RMON I and II standards, SNMPv1/v2/v3, MEF9, MEF14
-----------------------	--

Corporate and Sales Headquarters  
Orion Networks  
4262 Entry Ct STE K  
Chantilly, VA 20151 USA  
Phone: 512.646.4025  
[www.orionnetworks.com](http://www.orionnetworks.com)

To purchase Orion Networks solutions, please contact your Orion Networks representative or authorized reseller.

Copyright 2013 Orion Networks. All rights reserved. Orion Networks, the Orion Networks logo are registered trademarks of Orion Networks. in the United States and other countries. All other trademarks, service marks, or registered service marks are the property of their respective owners. Orion Networks assumes no responsibility for any inaccuracies in this document. Orion Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

June 2013